



Magnum Vertical PTO Pump

- 140-250 HP+ Model for Commercial Scale Farms & Hauling Operations
- Hydraulic Controls for Optional Nozzle Agitation & Valves
- 8" Manifold for Quick Loading
- Pictured with Optional Double Valve Outlet
- Heavy Duty Gearbox for 300+ rated capacity
- Heavy Duty 2 pt Mount
- Multi Depth Design



Standard Vertical PTO Pump

- 50 - 120 HP Model for Traditional Dairy Operations & Standard Use
- Manual Controls for Optional Nozzle Agitation & Valves
- 6" Manifold Handles Standard Operation Demands
- 2 pt or Axle Mount
- Lighter Duty Pump for Easy Transport



Vertical PTO

Standard and Magnum



Standard Features:

- Straight Wall Pit Pumping & Agitation, 6'-14' Depths
- Available in Customizable Configurations
- Normal Lifespan of 20 Years or More
- 540 RPM or 1000 RPM Operating Speed
- Abrasive Resistant Steel for Sand-laden Manure Applications
- Double Grease Guns Supply Lubrication to Bearing & Seal Kit
- Quick Service to Seal Kit & Bearing without Removing Housing or Oil Chamber Assemblies
- 2 PT or 3 PT Hitch Styles Available
- 1.75" Driveline
- 6" Beam, 1/4" Wall Thickness
- N-TECH Impeller Leads Industry in Dairy Manure
- Handle Solids without Plugging
- Aggressive Pre-Agitator for Shredding



Options:

- 75-200 HP Options
- 26" Impeller and AR Housings for Sand Laden Manure
- 2 PT, 3 PT or Stationary
- Remote Hydraulic Control
- Rotating Manifold with Single or Double Agitators; All Motions Hydraulic
- Double Valve Option

